

shelf-securing position. For ease in installation, a slightly offset end extension 88 is formed on tip 82 so that it can be initially engaged or seated in aperture 86 when clip 78 is thereafter urged forwardly until tip 80 engages aperture 84.

In the Claims:

Please cancel claims 4-7.

Please re-write claims 8, 9 12 and 13 as follows:

8. (four times amended) A rotary shelf assembly mechanism comprising: a ~~vertical post arrangement~~ ^{telescopically adjustable}; first and second mounting brackets spaced apart from and opposing each other supporting the post arrangement; at least one single piece shelf connected to the post arrangement, the post arrangement having pin-receiving apertures proximate the at least one connected shelf, each of the at least one shelf having a post-securing section including a hub and a pin-receiving indent within the hub; and a pin extending through the post arrangement pin-receiving apertures, and cooperatively received and retained by the pin-receiving indent of the at least one shelf to secure the at least one shelf to the post arrangement ^{so that the post arrangement and the shelf rotate as one unit.} wherein the ~~post arrangement includes a post-encircling sleeve, the at least one pin-receiving indent connecting with the post-encircling sleeve to cooperatively receive the pin within the at least one indent and the post-encircling sleeve, through the post arrangement pin-receiving apertures and through the post.~~

2. (four times amended) The mechanism as claimed in claim 8 wherein the pin is an elongated element having first and second ends and the

F8
cancel G

at least one of
pin-receiving indent engages the pin ends when the pin operably secures the at least one shelf to the post arrangement.

Please cancel claim 10.

F9

~~3~~

(four times amended) The mechanism as claimed in claim 8

G wherein the hub of the at least one shelf has a post-receiving opening, the ^{pin}post-receiving indent is a rectangularly shaped recess communicating with the post-

G receiving opening, the post arrangement ^{further including} has pin-receiving apertures at each of a plurality of shelf positions.

G ~~the least one shelf positions and the pin is cooperatively received by the shelf hub,~~

G ~~the post-securing indent and the post pin receiving apertures to secure the at~~

G ~~least one shelf to the post.~~

~~4~~

(four times amended) The mechanism as claimed in claim ~~11~~ ³

wherein the pin is an elongated element having first and second ends and the pin-receiving indent engages at least one of the pin ends when the pin operably secures the at least one shelf to the post arrangement.

13. (twice amended) The mechanism as claimed in claim 8 wherein

the pin-receiving indent includes a post- encircling sleeve and at least one pin-receiving indent connecting with the post-encircling sleeve to cooperatively receive the pin within the at least one pin-receiving indent, through the post-encircling sleeve and through the post arrangement pin-receiving apertures and the post, the hub of the at least one shelf has a post-receiving opening and the

F0

EXPRESS MAIL LABEL NO. E4346709710US

410
cancel

post-securing indent is a rectangularly shaped recess communicating with the post-receiving opening and the post arrangement has pin-receiving apertures and the pin is cooperatively received by the shelf hub, the post securing indent and the post pin-receiving apertures to secure the at least one shelf to the post.
